


CONSTRUCTION NOTES:

1. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POST WITH WIRES TIES OR STAPLES.
2. FILTER FABRIC TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION.
3. WHEN TWO SECTIONS OF FILTER FABRIC ADJOIN EACH OTHER, THEY SHALL BE OVERLAPPED BY 6" AND FOLDED.
4. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.
5. INSPECTION SHALL BE FREQUENT AND REPAIR/REPLACEMENT SHALL BE MADE PROMPTLY AS NEEDED.
6. FENCES SHALL BE REMOVED WHEN THEY HAVE SERVED THEIR USEFULNESS SO AS NOT TO BLOCK OR IMPEDE STORM FLOW OR DRAINAGE.

DRAFT

 <p>TOWN OF WAKEFIELD</p>	ENGINEERING DIVISION - WAKEFIELD PUBLIC WORKS		
	DESIGN AND CONSTRUCTION STANDARDS SILTATION FENCE DETAIL		
	SCALE: NTS	DETAIL #: EC-03	DATE: JUN 15 2022